

# Carbon Dioxide

*Manufactured and Tested to  
ANSI/UL Standards  
ISO-9001:2000 / ISO-14001:2004 Certified*  
**UL LISTED, FM AND USCG APPROVED**

- ★ Rust free aluminum cylinders - up to 30% lighter than steel cylinders
- ★ All Metal Valve Construction
- ★ Meets many hospital medical equipment requirements
- ★ Model 322 independently tested and approved for use in MRI facilities
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -40°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label

SPECIFICATIONS	CARBON DIOXIDE			
	5	10	15	20
Size & Capacity (lbs.)	5	10	15	20
Application	Horn	Hose & Horn		
Model Number	322	330	331	332
U/L Rating	5B:C	10B:C	10B:C	10B:C
Shipping Weight (lbs.)	14	28 <sup>1</sup> / <sub>4</sub>	37 <sup>1</sup> / <sub>4</sub>	50 <sup>1</sup> / <sub>4</sub>
Height (in.)	17 <sup>1</sup> / <sub>4</sub>	24	30	30
Width (in.)	8 <sup>1</sup> / <sub>4</sub>	12	12	13
Depth (Diam. - in.)	5 <sup>1</sup> / <sub>4</sub>	7	7	8
Range (ft.)	3-8			
Discharge Time (sec.)	10	10	12 <sup>1</sup> / <sub>2</sub>	19
F. M. Approved	Yes			
Standard Bracket	Wall			



**NON-MAGNETIC MODEL AVAILABLE:  
MODEL 322NM**

**Carbon Dioxide** is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

**Also available in 50 / 100 lb.  
wheeled extinguishers and  
100 lb. stationary.**

**5 YEAR WARRANTY**