

WHEELED FIRE EXTINGUISHERS FROM AMEREX

Amerex portable fire extinguishers have been the industry standard for 50 years. Since 1971, our commitment to quality, service, and innovation is unmatched. ***Quality is Behind the Diamond***-in every product.

People never think twice about fire extinguishers until they need one, but when they need one, the extinguisher must work. At Amerex, we all work together to make sure we're delivering the best quality products available. From our quality audits at each level of production to shipping preparations before leaving

the warehouse, you know the products you receive are what you have come to expect from Amerex. With warehouses located in Oakland, New Jersey, Elk Grove Village, Illinois, Santa Fe Springs, California and Trussville, Alabama, you are assured that product lead times are at a minimum.

Amerex Corporation

www.amerex-fire.com
sales@amerex-fire.com
+1 205.655.3271



Longer life, lower cost and the best warranty in the industry—
that's quality behind the diamond.



All Amerex Fire Extinguishers comply with the recommendations of the **National Fire Protection Association** and are tested and rated by **Underwriters Laboratories** or **FM Global** to **ANSI / UL Standards**. All extinguisher nameplates contain the necessary HMIS information to comply with national and local OSHA requirements.

WHERE TO USE

Amerex manufactures an extensive variety of hand-portable and wheeled fire extinguishers, both “compliance” (code required) and “specialty” types.

“Compliance” extinguishers are designed to meet and exceed state or local fire protection requirements. “Specialty” extinguishers are intended for use on particular types of hazards. Careful attention should be paid to locating them in close proximity to the specific hazard they are meant to protect. It is natural for a person to use the extinguisher located nearest to a fire. The most current issue

of NFPA-10 should be consulted for minimum recommended fire extinguisher types, placement, and travel distances. Your local Amerex Fire Equipment Distributor is professionally equipped to help you evaluate and implement these recommendations. All “Pictograms” are detailed below and should be reviewed with all who might be expected to use a fire extinguisher. Everyone should

be familiar with these picture symbols which identify the types of fires on which they may be used. The international sign system diagonal red slash indicates a potential danger if the extinguisher is used on that particular type of fire.

Types of Fires			
Class A	Ordinary combustibles	Wood, paper, rubber, fabrics, and many plastics	
Class B	Flammable liquids & gases	Gasoline, oils, paint, lacquer, and tar	
Class C	Live electrical equipment	Fires involving live electrical equipment	
Class D	Combustible metals or combustible metal alloys	NO picture symbol	
Class K	Fires in cooking appliance that involve combustible cooking media	Vegetable or Animal Oils and Fats	

Types of Extinguishers	
Class A	
Class A:B	
Class A:B:C	
Class A:C	
Class B:C	
Class D	
Class A:K	

HOW TO USE

All Amerex extinguishers are furnished with a detailed “Owners Manual” containing valuable information. The manual contains information on the installation, use, and maintenance of the extinguisher. The extinguisher nameplate contains specific information on “HOW TO USE” the particular extinguisher. The label instructions vary slightly according to type and size. All potential operators should be totally familiar with the instructions on any extinguisher they might be required to use.



APPLICATIONS



Healthcare

Aluminum Valve Dry Chemical, CO2, Clean Agent, K Class, Water Mist, Wheeled



Transportation

ABC Dry Chemical—All varieties (OEM, Up-fitters, Aftermarket)



Industrial

Light: Aluminum Valve Dry Chemical, Clean Agent, CO2, Class D

Medium: Aluminum Valve Dry Chemical, Clean Agent, CO2, Class D

Heavy: Brass Valve Dry Chemical, Z-Series, Class D, Wheeled



Education

Aluminum Valve Dry Chemical, Clean Agent, K class, Water Mist, CO2, Restaurant Systems



Oil and Gas

Brass Valve Dry Chemical, Z-Series, Wheeled



Chemical

Brass Valve Dry Chemical, Z-Series, Wheeled



Distribution Centers

Brass Valve Dry Chemical, Z-Series, Wheeled

STORED PRESSURE

50 & 125lb. Stored Pressure–ABC and PURPLE K Dry Chemical

These commercial stored pressure extinguishers are available in a choice of two sizes and chemical options. The carriage design on both sizes provides cage type protection for the agent cylinder as well as a well-balanced platform for transportation and operation. The narrow width and easy rolling semi-pneumatic rubber tire wheels allow one person movement through narrow aisles, doorways, and in confined areas. Chemical and pressure is sealed in the agent cylinder, ready for instant actuation and is always protected from contamination. Stored-pressure wheeled extinguishers are less expensive to purchase as well as easier and less costly to maintain and service.



FEATURES:

- Brass hose fittings
- Quick-opening valves
- Live swivel on discharge valve
- Brass valve–chrome plated on 125 lb. models
- Lifting eyes on 125 lb. models
- Heavy-duty steel cylinder, carriage, hose rack
- DOT/TC cylinders
- UL/ULC label with QR code
- Large instruction pictogram
- Chrome-forged brass fill cap on 125 lb. models
- Large fill opening on 125 lb. models
- Stainless-steel fasteners
- Stainless-steel gauge guard on 125 lb. models
- 6-Year Warranty



SPECIFICATIONS	50 LB. DRY CHEMICAL		125/150 LB. DRY CHEMICAL	
MODEL NUMBER	495	497	488	490
AGENT TYPE	ABC	PURPLE K	ABC	PURPLE K
UL & ULC RATING	20A:160B:C	160B:C	30A:240B:C	320B:C
CAPACITY (LBS. / KG)	50 / 22.68		125 / 56.7	
SHIPPING WT. (LBS. / KG)	174 / 78.88		344 / 155.95	
HEIGHT (IN. / CM)	46 / 116.84		53.5 / 136.0	
WIDTH (IN. / CM)	21.5 / 54.61		28 / 71.12	
DEPTH (IN. / CM)	24 / 60.96		40 / 101.6	
DISCHARGE TIME (SEC.)	35	33	49	52
DISCHARGE RANGE (FT. / M)	25-35 / 7.62 - 10.66		30-40 / 9.1-12.2	
OPERATING TEMP. (F / C)	-40° TO +120° / -40° TO +49°		-65° TO 120° / -54° TO +49°	
HOSE LENGTH (FT. / M)	25 / 7.62		50 / 15.2	
HOSE DIAMETER (IN. / CM)	.50 / 1.27		.75 / 1.90	
WHEELS [SEMI-PNEU] (IN. / CM)	12.5 X 3.5 / 31.75 X 8.89		16 X 4 / 40.64 X 10.16	
USCG APPROVED	YES			

CONFORMS TO TEST STANDARDS:
CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

HIGH-PERFORMANCE Z-SERIES WHEELED EXTINGUISHERS

HIGH-PERFORMANCE 125 & 250 lb. –ABC and PURPLE K Dry Chemical

Just like our hand-held units, High-Performance Z-Series wheeled extinguishers offer superior reliability, corrosion resistance, and affordable maintenance costs.



FEATURES:

- Proprietary corrosion-resistant paint process
- Integral lift loops for loading/positioning on board
- Carriage design rests the agent cylinder and hose above ground for protection
- Chrome-plated brass shut-off ball valve with swivel pistol grip
- Separate 3" fill port with chrome-plated brass cap
- 1" x 50' field-repairable hose constructed with brass couplings
- Full 250 lb. fill regardless of the type of chemical used – no "nominal" fill sizes
- Large, easy-to-read pressure gauge with stainless-steel gauge guard
- Wide-footprint wheels at 36" x 6" for easy movement of unit
- 12-Year Warranty



SPECIFICATIONS	DRY CHEMICAL		
MODEL NUMBER	756	758	759
AGENT TYPE	ABC	PURPLE K	PURPLE K
UL & ULC RATING	40A:160B:C	160B:C	120B:C
CAPACITY (LBS. / KG)	250 / 113.4		125 / 56.7
SHIPPING WT. (LBS. / KG)	775 / 351.3		400 / 181.4
HEIGHT (IN. / CM)	60 / 152.4		53.5 / 135.9
WIDTH (IN. / CM)	37 / 93.98		34 / 86.4
DEPTH (IN. / CM)	44 / 111.76		38.5 / 97.8
DISCHARGE TIME (SEC.)	50	38	30
DISCHARGE RANGE (FT. / M)	60 - 80 / 18.19 - 24.26		50 - 55 / 15.24 - 16.76
OPERATING TEMP. (F / C)	-40° to +120° / -40° to +49°		
HOSE LENGTH (FT. / M)	50 / 15.24		
HOSE DIAMETER (IN. / CM)	1 / 2.54		
WHEELS [STEEL] (IN. / CM)	36 X 6 / 91.44 X 15.24		
FLOW RATE (LBS./SEC.)	4.8	6.6	5.2
USCG APPROVED	YES		

CONFORMS TO TEST STANDARDS:
CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

DIRECT PRESSURE

125 & 300 lb. Direct Pressure–ABC, PURPLE K Dry Chemical

Direct Pressure extinguishers utilize a 23ft³ nitrogen cylinder with a “quick-opening brass valve” to pressurize and completely discharge the agent cylinder. The compact size and 16” semi-pneumatic tires allow easy maneuvering and operation by one person, through narrow doorways and aisles. A 4” stainless-steel fill opening with rugged chrome-plated brass cap makes servicing easier. For large hazards, choose the 300 lb. ABC or Purple K Direct Pressure extinguishers with a “quick-opening” 55ft³ nitrogen cylinder. They provide quality and economical fire protection, large volume capacity for extra-high hazard areas with single-person transport and operation. The 36” X 6” wide steel wheels make movement possible in sandy or soft soil.



FEATURES:

- Stainless-steel collars
- Chrome-plated brass fill caps
- Brass hose fittings
- Live swivels on discharge valve
- Heavy-duty steel cylinder, carriage, hose rack
- Lifting eyes
- UL/ULC label with QR code
- Large instruction pictogram
- DOT/TC nitrogen cylinder with quick-opening brass valve
- 6-Year Warranty



SPECIFICATIONS	125 LB. DRY CHEMICAL		300 LB. DRY CHEMICAL	
MODEL NUMBER	450	452	491	493
AGENT TYPE	ABC	PURPLE K	ABC	PURPLE K
UL & ULC RATING	30A:240B:C	320B:C	40A:320B:C	320B:C
CAPACITY (LBS./KG)	125 / 57		300 / 136.07	
SHIPPING WT. (LBS./KG)	335 / 152		743 / 337.01	
HEIGHT (IN. / CM)	45 / 115		57 / 144.78	
WIDTH (IN. / CM)	24 / 61		34 / 86.36	
DEPTH (IN. / CM)	36 / 92		39 / 99.06	
DISCHARGE TIME (SEC.)	52	52	60	67
DISCHARGE RANGE (FT. / M)	30 - 40 / 9 - 12			
OPERATING TEMP. (F / C)	-65° to +120° / -54° to +49°			
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651		55 / 1557.43	
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450			
HOSE LENGTH (FT. / M)	50 / 15.24			
HOSE DIAMETER (IN. / CM)	.75 / 1.90		1 / 2.54	
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.16		36 X 6 / 91.44 X 15.24	
USCG APPROVED	YES			

CONFORMS TO TEST STANDARDS:
CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

HALOTRON I™ EXTINGUISHERS

65 lb. & 150 lb.–Stored-Pressure Halotron I™

The Amerex Halotron I™ extinguishers feature the same qualities found in all Amerex products and adds the convenience of a “clean” extinguishing agent. Halotron I™ extinguishing agent has proven itself as the leader in the hunt for an alternative “clean” agent by being the only alternative “clean” agent to obtain FAA approvals for both ramp use (ARFF Vehicle) and on-board an aircraft. Combining the quality of Amerex products with a proven alternative “clean” agent, the Amerex Halotron I™ wheeled extinguishers offer you the best value in the industry.



FEATURES:

- Brass hose fittings
- Live swivels on discharge valve
- Reflective stripes
- Tow loops
- Stainless-steel fasteners
- Heavy-duty steel cylinder, carriage, hose rack
- DOT/TC cylinders
- Stainless-steel gauge guard
- Quick-opening valves
- Chrome-plated brass valve
- Quick-release discharge hose
- UL/ULC label with QR code
- Large instruction pictogram
- EPA-approved “Clean Agent” for Class A, B, and C hazards
- Low GWP (Global Warming Potential)
- Low ODP (Ozone Depletion Potential)
- Short atmospheric lifetime
- Maximum visibility during discharge
- No thermal or static shock
- No electrical conductivity back to the operator
- 6-Year Warranty

SPECIFICATIONS	HALOTRON I™		
	B673	B674	B675
MODEL NUMBER	B673	B674	B675
AGENT TYPE	CLEAN AGENT		
UL & ULC RATING	4A:80B:C	10A:120B:C	
CAPACITY (LBS. / KG)	65 / 29.5	150 / 68	
SHIPPING WT. (LBS. / KG)	286 / 129.7	512 / 232.2	610 / 276.7
HEIGHT (IN. / CM)	58 / 147.3	64 / 162.6	
WIDTH (IN. / CM)	28 / 71.1	30 / 76.2	37 / 94
DEPTH (IN. / CM)	39 / 99.1	42 / 106.7	43 / 109.2
DISCHARGE TIME (SEC.)	22	38	
DISCHARGE RANGE (FT. / M)	30 - 45 / 9.1 - 13.7		
OPERATING TEMP. (F / C)	-40° to 120° / -40° to +49°		
HOSE LENGTH (FT. / M)	50 / 15.2		
HOSE DIAMETER (IN. / CM)	.75 / 1.9		
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM) WITH NON-SPARKING RUBBER TREADS	16 X 4 / 40.64 X 10.2		36 X 2.5 / 91.44 X 6.35
USCG APPROVED	YES		

CONFORMS TO TEST STANDARDS:
CAN/ULC S566 & ANSI/UL 2129
CAN/ULC S508 & ANSI/UL 711

NOVEC 1230™ EXTINGUISHERS

3M™ NOVEC 1230™ Fire Protection Fluid

This extinguishing agent has a Global Warming Potential of 1 and an atmospheric life of just five days making it the long-term sustainable choice that also has the greatest margin of safety of any of the chemical agents in the marketplace today.



FEATURES:

- Environmentally friendly 3M™ Novec™ 1230 Clean Agent (0 ODP - 1 GWP)
- Brass, chrome-plated operating valve
- 125 PSI operating pressure
- Heavy-duty steel cylinder, carriage, and hose hanger assembly
- DOT Cylinders
- Quick-release 40ft. discharge hose with brass/chrome-plated ball-type shut-off nozzle
- Pressure gauge protected by a stainless-steel gauge guard
- corrosion-resistant lime/yellow polyester paint finish
- UL/ULC label with QR code
- Large instruction pictogram
- Operating temperature range: -40° to +120° F.
- 6-Year Warranty

SPECIFICATIONS	3M™ Novec 1230™
MODEL NUMBER	775
AGENT	Novec 1230
CAPACITY (LBS.)	150
UL & ULC RATING	3A:80B:C
SHIPPING WEIGHT (LBS.)	395
DISCHARGE TIME (SEC.)	22
CYLINDER - DOT 4BW240	
OPERATING PRESS (PSI)	125
TEST PRESSURE (PSI)	480
BURST PRESSURE (MINIMUM - PSI)	960
DISCHARGE RANGE (FT.)	30
HOSE LENGTH (FT.)	40
HOSE DIAMETER (IN.)	1.0
WHEELS SEMI-PNEUMATIC (IN.)	16 x 4
HEIGHT (IN.)	61
WIDTH (IN.)	29
DEPTH (IN.)	42
USCG APPROVED	YES

CONFORMS TO TEST STANDARDS:

CAN/ULC S566 & ANSI/UL 2129
CAN/ULC S508 & ANSI/UL 711

CARBON DIOXIDE EXTINGUISHERS

50 & 100 lb. CARBON DIOXIDE

Large volume CO₂ protection provided in either 50 or 100 lb. (2-50 lb. cylinders) wheeled extinguishers. Rugged construction and easy to operate with a "quick-opening" "T" handle valve and horn mounted shut-off valve. A logical choice in areas where a Class B:C non-contaminating agent is required and where hand-portable extinguishers do not provide adequate protection.



FEATURES:

- Heavy-duty steel carriages
- Quick-opening brass valve
- Squeeze-grip chrome-plated discharge valve
- Reinforced wire-braided hose and shock-resistant horn to reduce static electricity
- Brass hose fittings
- UL/ULC label with QR code
- Large instruction pictogram
- DOT/TC cylinder with quick-opening brass valve
- Clean, non-contaminating odorless gas
- 5-Year Warranty



SPECIFICATIONS	CARBON DIOXIDE	
MODEL NUMBER	333	334
AGENT TYPE	CARBON DIOXIDE	
UL & ULC RATING	20B:C	
CAPACITY (LB. / KG)	50 / 22.7	100 / 45.4
SHIPPING WT. (LB. / KG)	257 / 116.6	461 / 209.3
HEIGHT (IN. / CM)	47 / 119.5	
WIDTH (IN. / CM)	23 / 58.4	
DEPTH (IN. / CM)	48 / 122	
DISCHARGE TIME (SEC.)	44+-5	74 +-8
DISCHARGE RANGE (FT. / M)	10 - 15 / 3.04 - 4.57	
OPERATING TEMP. (F / C)	-22° to +120° / -30° to +49°	
HOSE LENGTH (FT. / M)	40 / 12.1	
HOSE DIAMETER (IN. / CM)	.5 / 1.27	
WHEELS [SEMI-PNEUMATIC] (IN. / CM)	16 X 4 / 40.64 X 10.16	
USCG APPROVED	YES	

CONFORMS TO TEST STANDARDS:
 CAN/ULC S503 & ANSI/UL 154
 CAN/ULC S508 & ANSI/UL 711

CLASS D EXTINGUISHERS

150 lb. Regulated Pressure SODIUM CHLORIDE

250 Lb. Regulated Pressure COPPER POWDER

Two choices for large volume Class D (flammable metal) protection. Model 680 (Sodium Chloride) is effective on magnesium, sodium, potassium, and sodium potassium alloy fires. Model 681 (Copper Powder) designed specifically for fighting difficult lithium fires. Well balanced for quick transport on 36" non-sparking rubber tread steel wheels. Both are pressurized with Argon and regulated to a low 125 psi to avoid disrupting the burning materials.



FEATURES:

- Stainless-steel collars
- Chrome-plated brass fill caps
- Brass hose fittings
- Live swivels on discharge valve
- Heavy-duty steel cylinder, carriage, hose rack
- FM label with QR code
- Large instruction pictogram
- DOT/TC argon cylinder with quick-opening brass valve
- Brass regulator
- Extention wand included (nozzle sold separately)
- 6-Year Warranty

SPECIFICATIONS	CLASS D	
MODEL NUMBER	680R	681R
AGENT TYPE	SUPER D (SODIUM CHLORIDE)	COPPER
CAPACITY (LB.)	150 / 68	250 / 113.33
SHIPPING WT. (LBS. / KG)	444 / 201.28	544 / 246.61
HEIGHT (IN. / CM)	52 / 132.08	
WIDTH (IN. / CM)	28 / 71.12	
DEPTH (IN. / CM)	45 / 114.3	
DISCHARGE TIME (SEC.)	80	120
DISCHARGE RANGE (FT./M) WITH APPLICATOR	4 - 8 / 1.31 - 2.62	
OPERATING TEMP. (F / C)	-40° to 120° / -40° to +49°	
ARGON CYLINDER (CU. FT. / LITER)	110 / 3115	
HOSE LENGTH (FT. / M)	25 / 7.70	
HOSE DIAMETER (IN. / CM)	.75 / 1.90	
WHEELS [STEEL] (IN. / CM) WITH NON-SPARKING RUBBER TREADS	36 X 2.5 / 91.44 X 6.35	
USCG APPROVED	NO	
FM APPROVED	YES	

CONFORMS TO TEST STANDARDS:
CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711